Suction cup F50-2 Nitrile-PVC, 1/8" NPSF female, with cone valve, 3150051P



- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

General

| Curve radius | 55 mm |
|-------------------------|--------------------|
| Movement, vertical max. | 2.2 mm |
| Application | Dry sheet metal |
| Material | Nitrile-PVC (NPV) |
| Suction cup model | F |
| Suction cup shape | Flat |
| Volume | 10 cm ³ |
| Weight | 14 g |

Fitting

| Fitting size | 1/8" |
|----------------|-------------|
| Fitting style | Female |
| Fitting type | NPSF-thread |
| Fitting option | Cone valve |

Dimension

| Height | 26 mm |
|--------------------------|---------|
| Outer diameter | 53 mm |
| Outer diameter, actuated | 54.6 mm |

Performance — lifting forces

| | ± | _ |
|---------|----------|----------|
| 20 -kPa | 36 N | 24 N |
| 60 -kPa | 74 N | 40 N |
| 90 -kPa | 96 N | 50 N |


Material

| | Nitrile-PVC (NPV) |
|-------------|-------------------|
| Colour | Black |
| Hardness | 50 °Shore A |
| Temperature | 0 – 90 °C |

Material resistance

| | Nitrile-PVC (NPV) |
|--------------------|-------------------|
| Alcohol | ++ |
| Concentrated acids | + |
| Ethanol | N/A |
| Hydrolysis | ++ |
| Methanol | N/A |
| Oil | +++ |
| Oxidation | ++ |
| Petrol | +++ |
| Wear resistance | +++ |
| Weather and ozone | ++ |

Dimensional drawings



Values specified in the data sheet are tested at:

| Room temperature | (20°C [68°F] ± 3°C [5.5°F]) |
|------------------------|--|
| Standard atmosphere | (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]) |
| Relative humidity | 0-100% |
| Compressed air quality | DIN ISO 8573-1 class 4 |

Spare parts

| | Item no. |
|---|----------|
| Suction cup F50-2 Nitrile-PVC | 0101137 |
| Fitting 1/8" NPSF female, 50, with cone valve | 0101157 |

Accessories

| | Item no. |
|--|----------|
| Suction cup F50-2 Silicone | 0101138 |
| Suction cup F50-2 HNBR | 0108166 |
| Suction cup F50-2 Nitrile-PVC, for fitting with cone valve | 3150241P |
| Suction cup F50-2 Silicone, for fitting with cone valve | 3150241S |
| Fitting G3/8" male, 50, with mesh filter and dual flow control valve | 3251015 |
| Fitting G3/8" male, 50, with mesh filter | 3250087 |
| Fitting G1/4" male, with mesh filter and dual flow control valve | 3251013 |
| Fitting G1/4" male, 50, with mesh filter | 3250092 |
| Fitting 5x1/8" NPSF female, 50, with dual flow control valve | 3251017 |
| Fitting 5x1/8" NPSF female, 50 | 0100262 |
| Fitting 3/8" NPT male, with mesh filter | 3250090 |
| Fitting 3/8" NPT male, with dual flow control valve | 3251016 |
| Fitting 1/8" NPSF female, 50, with mesh filter | 0101154 |
| Fitting 1/8" NPSF female, 50, with dual flow control valve | 3251012 |
| Fitting 1/8" NPSF female, 50, PA | 3150198 |
| Fitting 1/8" NPSF female, 50 | 3250017 |
| Fitting 1/4" NPT male, with mesh filter | 3250094 |
| Fitting 1/4" NPT male, with dual flow control valve | 3251014 |
| | |