# Suction cup B75-2 Nitrile-PVC with filter, 0101942



- Suitable for level adjustment. Several short bellows in one lifting device can handle objects with height differences and varying shapes, for example embossed or corrugated plates.
- Lifting movement to separate small and thin objects.
- Only lightweight objects should be handled when the lifting force is parallel to the surface of the object, in order to achieve good precision and safe lifting movement.

#### General

Curve radius	40 mm
Movement, vertical max.	24 mm
Application	Plastic injection molded parts, Dry sheet metal
Material	Nitrile-PVC (NPV)
Suction cup model	В
Suction cup shape	Bellows
Volume	110 cm <sup>3</sup>
Weight	35 g

## **Fitting**

Fitting size	None
Fitting style	None
Fitting type	None
Fitting option	None

#### **Dimension**

Height	37 mm
Outer diameter	78 mm

#### Performance — lifting forces

	<b>1</b>	<b>*</b>
20 -kPa	74 N	62.4 N
60 -kPa	167 N	122.4 N
90 -kPa	226 N	154.1 N


#### Material

	Nitrile-PVC (NPV)
Colour	Black
Hardness	50 °Shore A
Temperature	0 – 90 °C

### **Material resistance**

	Nitrile-PVC (NPV)
Alcohol	++
Concentrated acids	+
Ethanol	N/A
Hydrolysis	++
Methanol	N/A
Oil	+++
Oxidation	++
Petrol	+++
Wear resistance	+++
Weather and ozone	++

# Dimensional drawings



# Values specified in the data sheet are tested at:

Room temperature	(20°C [68°F] ± 3°C [5.5°F])
Standard atmosphere	$(101.3 [29.9 inHg] \pm 1.0 kPa [0.3 inHg])$
Relative humidity	0-100%
Compressed air quality	DIN ISO 8573-1 class 4

# Spare parts

	Item no.
Filter D=80, 10 pcs, for B75-2	0201149

## Accessories

	Item no.
Fitting 1/4" NPT female Al, with mesh filter & 10-32 addl. conn.	0127821
Fitting 1/8" NPSF female Al, with mesh filter	0127819
Fitting 75, 1/8" NPSF female, with mesh filter	0100548
Fitting 75, 3/8" NPSF female, with mesh filter	0100553
Fitting 75, G1/2" female, with mesh filter	0100555
Fitting 75, G3/8" female, with mesh filter	0100551
Fitting G1/2" female Al, with mesh filter	0127820