Suction cup B75P Polyurethane 60, thread insert G3/8" male with mesh filter, 0107319



- Suitable for level adjustment and for uneven and porous surfaces such as cardboard, etc.
- In the two-coloured suction cup the bellows and the sealing lip are of different hardnesses, which makes the suction cup strong and stable and, at the same time, soft and flexible.
- DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane.
- The material of the DURAFLEX® is mark free.

General

| Curve radius | 90 mm |
|-------------------------|--|
| Movement, vertical max. | 22.8 mm |
| Application | Mark Free, Plastic injection molded parts, Dry sheet metal |
| Material | Polyurethane (PU60) |
| Suction cup model | B-P |
| Suction cup shape | Bellows |
| Volume | 110 cm ³ |
| Weight | 72 g |

Fitting

| Fitting size | 3/8" |
|----------------|-------------|
| Fitting style | Male |
| Fitting type | G-thread |
| Fitting option | Filter mesh |

Dimension

| Height | 48.8 mm |
|----------------|---------|
| Outer diameter | 79 mm |

Performance — lifting forces

| | ± | ± |
|---------|----------|----------|
| 20 -kPa | 83 N | 121 N |
| 60 -kPa | 196 N | 229 N |
| 90 -kPa | 255 N | 298 N |


Material

| | Polyurethane (PU60) |
|-------------|---------------------|
| Colour | Green transparent |
| Hardness | 60 °Shore A |
| Temperature | 10 – 50 °C |

Material resistance

| | Polyurethane (PU60) |
|--------------------|---------------------|
| Alcohol | N/A |
| Concentrated acids | + |
| Ethanol | + |
| Hydrolysis | + |
| Methanol | - |
| Oil | +++ |
| Oxidation | - |
| Petrol | + |
| Wear resistance | +++ |
| Weather and ozone | +++ |

Dimensional drawings



Values specified in the data sheet are tested at:

| Room temperature | $(20^{\circ}C [68^{\circ}F] \pm 3^{\circ}C [5.5^{\circ}F])$ |
|------------------------|---|
| Standard atmosphere | (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]) |
| Relative humidity | 0-100% |
| Compressed air quality | DIN ISO 8573-1 class 4 |

Spare parts

| | | Item no. |
|----------------------------------|-----------------------------|----------|
| Suction cup B75F insert | Polyurethane 60, for thread | 0107318 |
| Thread insert G3, mesh filter | /8" male, with O-ring and | 0107148 |

Accessories

| | Item no. |
|--|----------|
| Suction cup B75P Polyurethane 30/60 | 0104723 |
| Suction cup B75P Polyurethane 60 | 0111594 |
| Suction cup B75P Polyurethane 30/60, for thread insert | 0106832 |
| Fitting 75, 1/8" NPSF female, with mesh filter | 0100548 |
| Fitting 75, 3/8" NPSF female, with mesh filter | 0100553 |
| Thread insert G3/8" male, with O-ring and mesh filter | 0107148 |
| Fitting 75, G1/2" female, with mesh filter | 0100555 |