

Item no: 3150131T

Suction cup F75 HNBR

Suitable for flat objects such as cardboard, sheet metal, glass and porous materials. The cleats stop deformation by preventing suction of the object into the cup. The suction cup has good stability and very little movement. Also suitable when the lifting force is parallel to the surface as the cleats increase friction.

- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force
 is parallel.

General

Application	HighLow rempCup, MarkFree, PlasticinjectionMoidedParts,

DrySheetMetal, GlassHandling

Suction cup shape

Material

Muterial

Suction cup model

F

Weight

Volume

Suction cup model

F75

Movement, vertical max.

Curve radius, min.

Flat

HNBR

F

E

F

F

Suction cup model

F75

Movement, vertical max.

To mm

Fitting

Fitting option None
Fitting size None
Fitting style None
Fitting type None

Dimension

Height	13 mm
Outer diameter, actuated	79 mm
Outer diameter	77 mm

Performance - lifting forces

	F75	$\stackrel{\bigstar}{ riangle}$	立
20 -kPa		80 N	60 N
60 -kPa		200 N	110 N
90 -kPa		270 N	140 N


Material

Name	HNBR75
Colour	BlueGrey
Temperature	-30 - 140 °C
Hardness	75 °Shore A

HNBR75

Alcohol	++
Concentrated acids	+
Ethanol	n/a
Hydrolysis	++
Methanol	n/a
Oil	+++
Oxidation	+++
Petrol	+++
Wear resistance	+++
Weather and ozone	+++

Dimensional drawings 🔓



Values specified in the data sheet are tested at:

- Room temperature: (20°C [68°F] ± 3°C [5.5°F])
- Standard atmosphere: (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
- Relative humidity: 0-100%
- Compressed air quality: DIN ISO 8573-1 class 4

Accessories

0127820 Fitting G1/2" female Al, with mesh filter
0100551 Fitting 75, G3/8" female, with mesh filter
0100552 Fitting 75, G3/8" female, with cone valve
0100555 Fitting 75, G1/2" female, with mesh filter
0100556 Fitting 75, G1/2" female, with cone valve
0100553 Fitting 75, 3/8" NPSF female, with mesh filter
0100548 Fitting 75, 1/8" NPSF female, with mesh filter
0127819 Fitting 1/8" NPSF female AI, with mesh filter
0127821 Fitting 1/4" NPT female Al, with mesh filter & 10-32 addl. conn.