Suction cup BL30-2 Silicone, G1/4" male, with mesh filter , 0101509



- Suitable for level adjustment.
- Lifting movement to separate small and thin objects.
- Less suitable when the lifting force is parallel to the surface of the object.

General

Curve radius	8 mm
Movement, vertical max.	20 mm
Application	Bag handling
Material	Silicone (SIL)
Suction cup model	BL-2
Suction cup shape	Multibellows
Volume	10 cm ³
Weight	7 g

Fitting

Fitting size	1/4"
Fitting style	Male
Fitting type	G-thread
Fitting option	Filter mesh

Dimension

Height	47.5 mm
Outer diameter	30 mm

Performance — lifting forces,

	±	*
20 -kPa	0.64 N	4.6 N
60 -kPa	1.6 N	9.5 N

Performance — lifting forces, reinforcement ring

	1
20 -kPa	6.4 N
60 -kPa	16 N


Material

	Silicone (SIL)
Colour	Red
Hardness	50 °Shore A
Temperature	-40 – 200 °C

Material resistance

	Silicone (SIL)
Alcohol	++
Concentrated acids	-
Ethanol	N/A
Hydrolysis	+
Methanol	N/A
Oil	-
Oxidation	+++
Petrol	-
Wear resistance	++
Weather and ozone	+++

Dimensional drawings



Values specified in the data sheet are tested at:

Room temperature	(20°C [68°F] ± 3°C [5.5°F])
Standard atmosphere	(101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
Relative humidity	0-100%
Compressed air quality	DIN ISO 8573-1 class 4

Spare parts

	Item no.
Fitting G1/4" male, 30–40, with mesh filter	3250091
Suction cup BL30-2 Silicone	0101118

Accessories

	Item no.
itting 1/4" NPT male, with dual flow control alve	3251008
itting 1/4" NPT male, with mesh filter	3250093
itting 1/8" NPSF female, 30–40	3250005
itting 1/8" NPSF female, 30–40, PA	3150197
itting 1/8" NPSF female, 30–40, with dual flow ontrol valve	v 3251006
itting 1/8" NPSF female, 30–40, with mesh lter	0101153
itting 3/8" NPT male, with dual flow control alve	3251010
itting 3/8" NPT male, with mesh filter	3250089
itting 5x1/8" NPSF female, 30–40	0100261
itting 5x1/8" NPSF female, 30–40, with dual low control valve	3251011
itting G1/4" male, 30–40, with mesh filter and ual flow control valve	3251007
itting G1/8" male, 40, with mesh filter	0200714
itting G3/8" male, 30–40, with mesh and dual low control valve	3251009
itting G3/8" male, 30–40, with mesh filter	3250086
uction cup BL30-2 Chloroprene	0101117
einforcement ring 30-2	3150072