



tandem flange
integrated wipers on both ends
lubrication hole M8 x1

Dimensions in mm

Part-No.	ϕd	$\phi D1$	$\phi D2$	D3	A	B	E1	E2	E3	E4	L	L1	$\phi d1$	M	N1	V	weight (kg)
FTAG-12	12	22	30	30	42	34	32	24	19	36	76	46	5,3	M6	13	10	0,20
FTAG-16	16	26	35	35	50	40	38	28	22	40	84	50	6,6	M8	18	10	0,32
FTAG-20	20	32	42	42	60	50	45	35	27	52	104	60	8,4	M10	22	10	0,55
FTAG-25	25	40	52	52	74	60	56	42	32	65	130	73	10,5	M12	26	10	1,17
FTAG-30	30	47	61	61	84	70	64	50	37	74	152	82	13,5	M16	34	10	1,50

- load ratings according to the specification of the bearing (x2)
- weight value considering the linear ball bushing, standard
- the bushings are secured in the housings by retaining rings DIN 471
- fixing screws DIN 912 - 8.8, circlip DIN 7980

Ordering code

FTAG-	ϕ -	S-	V
linear housing, tandem, flange	shaft diameter	<p>S linear ball bushing, self-aligning, high load capacity (refer to page 25)</p> <p>K linear ball bushing, standard (refer to p. 20)</p> <p>V linear ball bushing, all-steel (refer to page 21)</p> <p>KS linear ball bushing, standard, self-aligning (refer to page 24)</p> <p>FM linear slide bushing, self-lubricating (ref. to p. 27)</p> <p>L linear slide bushing, ceramic</p>	external front seal