piab Evolving automation



Item no: 0107325

Suction cup OBL40x90P Polyerethane 70, with 3 reinforcement plates and load support with G3/8" male, filter

Suitable for long, narrow and bent surfaces, for example bottles, pipes or sharply bent sheet parts. DURAFLEX® suction cups are manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material is mark-free.

- Suitable for long, narrow and bent surfaces, for example bottles, pipes or sharply bent sheet parts.
- Reinforcement plates gives stability to the suction cup.
- DURAFLEX® suction cups manufactured in a specially developed material that features the elasticity of rubber and wear resistance of polyurethane. The material does not leave any marks on the objects handled.

General


Application	Glass handling	
Suction cup shape	Oval Bellows	
Material	Polyurethane (PU70)	
Suction cup model	OBL	
Weight	77 g	
Volume	105 cm³	
Suction cup model	OBL40x90P PU70	
Movement, vertical max.	31 mm	
Curve radius, min.	28 mm	

Fitting

Fitting option	None
Fitting size	3/8"
Fitting style	Male
Fitting type	G-thread

Dimension

Dimension			
Height	73 mm		
Outer diameter	92.59 mm		
Performance - lifting forces			
OBL40x90P PU70	Â	à	
20 -kPa	49 N	45 N	
60 -kPa	117 N	97 N	
90 -kPa	178 N	135 N	
Material			
Name	PU70		
Colour	Black		
Temperature	10 - 50 °C		
Hardness	70 °Shore A		
	PU70		
Alcohol	n/a		
Concentrated acids	+		
Ethanol	+		
Hydrolysis	+		
Methanol	-		
Oil	+++		
Oxidation	-		
Petrol	+		
Wear resistance	+++		
Weather and ozone	+++		



Values specified in the data sheet are tested at:

- Room temperature: (20°C [68°F] ± 3°C [5.5°F])
- Standard atmosphere: (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
- Relative humidity: 0-100%
- Compressed air quality: DIN ISO 8573-1 class 4