Suction cup B75-2 Nitrile-PVC with filter, 0101942



- Suitable for level adjustment. Several short bellows in one lifting device can handle objects with height differences and varying shapes, for example embossed or corrugated plates.
- Lifting movement to separate small and thin objects.
- Only lightweight objects should be handled when the lifting force is parallel to the surface of the object, in order to achieve good precision and safe lifting movement.

General

Curve radius	40 mm
Movement, vertical max.	24 mm
Application	Plastic injection molded parts, Dry sheet metal
Material	Nitrile-PVC (NPV)
Suction cup model	В
Suction cup shape	Bellows
Volume	110 cm ³
Weight	35 g

Fitting

Fitting size	None
Fitting style	None
Fitting type	None
Fitting option	None

Dimension

Height	37 mm
Outer diameter	78 mm

Performance — lifting forces

	1	_
20 -kPa	74 N	62.4 N
60 -kPa	167 N	122.4 N
90 -kPa	226 N	154.1 N


Material

	Nitrile-PVC (NPV)
Colour	Black
Hardness	50 °Shore A
Temperature	0 - 90 °C

Material resistance

	Nitrile-PVC (NPV)
Alcohol	++
Concentrated acids	+
Ethanol	N/A
Hydrolysis	++
Methanol	N/A
Oil	+++
Oxidation	++
Petrol	+++
Wear resistance	+++
Weather and ozone	++

Dimensional drawings



Values specified in the data sheet are tested at:

Room temperature	(20°C [68°F] ± 3°C [5.5°F])
Standard atmosphere	(101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
Relative humidity	0-100%
Compressed air quality	DIN ISO 8573-1 class 4

Spare parts

	Item no.
Filter D=80, 10 pcs, for B75-2	0201149

Accessories

	Item no.
Fitting 1/4" NPT female Al, with mesh filter & 10-32 addl. conn.	0127821
Fitting 1/8" NPSF female Al, with mesh filter	0127819
Fitting 75, 1/8" NPSF female, with mesh filter	0100548
Fitting 75, 3/8" NPSF female, with mesh filter	0100553
Fitting 75, G1/2" female, with mesh filter	0100555
Fitting 75, G3/8" female, with mesh filter	0100551
Fitting G1/2" female Al, with mesh filter	0127820