Suction cup F-OB 30x60 Silicone, G1/4" male SS, FCM, 0207048



- The silicone material complies with FDA 21 CFR 177.2600 and EU 1935/2004.
- Transparent color without pigment
- Long lasting high-end silicone material
- Excellent grip on oblong parts such as flow-packs and stickpacks
- Available with threaded and integrated stainless steel fittings.
- Easy to clean with hygienic design. No dust/dirt pockets.

General

| Curve radius | 11 mm |
|-------------------------|---|
| Movement, vertical max. | 10.9 mm |
| Application | Food contact materials (FDA & EU), non-detectable |
| Material | ASTM 316L, Silicone (SIL non-detectable FCM) |
| Suction cup model | F-OB |
| Suction cup shape | Oval Bellows |
| Volume | 17.5 cm ³ |
| Weight | 67.1 g |

Fitting

| Fitting size | 1/4" |
|----------------|----------|
| Fitting style | Male |
| Fitting type | G-thread |
| Fitting option | None |

Dimension

| Height | 49.9 mm |
|--------|---------|
| Length | 62 mm |
| Width | 32 mm |

Performance — lifting forces

| | ± | _ |
|---------|----------|----------|
| 10 -kPa | 8 N | 8.1 N |
| 20 -kPa | 17.2 N | 13.4 N |
| 40 -kPa | 31.1 N | 27.5 N |


Material

| | Silicone (SIL non-detectable FCM) |
|-------------|-----------------------------------|
| Colour | Transparent |
| Hardness | 40 °Shore A |
| Temperature | -40 – 200 °C |

Material resistance

| | Silicone (SIL non-detectable FCM) |
|--------------------|-----------------------------------|
| Alcohol | ++ |
| Concentrated acids | - |
| Ethanol | N/A |
| Hydrolysis | + |
| Methanol | N/A |
| Oil | - |
| Oxidation | +++ |
| Petrol | - |
| Wear resistance | ++ |
| Weather and ozone | +++ |

Dimensional drawings



Values specified in the data sheet are tested at:

| Room temperature | (20°C [68°F] ± 3°C [5.5°F]) |
|------------------------|--|
| Standard atmosphere | (101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg]) |
| Relative humidity | 0-100% |
| Compressed air quality | DIN ISO 8573-1 class 4 |