Suction cup F40-2 Silicone, 0101136

- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.



General

Curve radius	52 mm
Movement, vertical max.	1.8 mm
Application	Dry sheet metal
Material	Silicone (SIL)
Suction cup model	F
Suction cup shape	Flat
Volume	4.8 cm ³
Weight	5.5 g

Fitting

Fitting size	None
Fitting style	None
Fitting type	None
Fitting option	None

Dimension

Height	13 mm
Outer diameter	42 mm
Outer diameter, actuated	43.7 mm

Performance — lifting forces

	±	_
20 -kPa	20 N	15 N
60 -kPa	40 N	25 N
90 -kPa	50 N	30 N


Material

	Silicone (SIL)
Colour	Red
Hardness	50 °Shore A
Temperature	-40 – 200 °C

Material resistance

	Silicone (SIL)
Alcohol	++
Concentrated acids	-
Ethanol	N/A
Hydrolysis	+
Methanol	N/A
Oil	-
Oxidation	+++
Petrol	-
Wear resistance	++
Weather and ozone	+++

Dimensional drawings



Values specified in the data sheet are tested at:

Room temperature	(20°C [68°F] ± 3°C [5.5°F])
Standard atmosphere	(101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
Relative humidity	0-100%
Compressed air quality	DIN ISO 8573-1 class 4

Accessories

Item no.
3250086
3251009
3251007
3250091
3251011
0100261
3250089
3251010
0101153
3251006
0101156
3150197
3250005
3250093
3251008