
Suction cup F50-2 Nitrile-PVC, 0101137

- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.



General

Curve radius	55 mm
Movement, vertical max.	2.2 mm
Application	Dry sheet metal
Material	Nitrile-PVC (NPV)
Suction cup model	F
Suction cup shape	Flat
Volume	10 cm ³
Weight	14 g

Fitting

Fitting size	None
Fitting style	None
Fitting type	None
Fitting option	None

Dimension

Height	17.5 mm
Outer diameter	53 mm
Outer diameter, actuated	54.6 mm

Performance — lifting forces

	±	_
20 -kPa	36 N	24 N
60 -kPa	74 N	40 N
90 -kPa	96 N	50 N


Material

	Nitrile-PVC (NPV)
Colour	Black
Hardness	50 °Shore A
Temperature	0 - 90 °C

Material resistance

	Nitrile-PVC (NPV)
Alcohol	++
Concentrated acids	+
Ethanol	N/A
Hydrolysis	++
Methanol	N/A
Oil	+++
Oxidation	++
Petrol	+++
Wear resistance	+++
Weather and ozone	++

Dimensional drawings



Values specified in the data sheet are tested at:

Room temperature	(20°C [68°F] ± 3°C [5.5°F])
Standard atmosphere	(101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
Relative humidity	0-100%
Compressed air quality	DIN ISO 8573-1 class 4

Accessories

Item no.
3251015
3250087
3251013
3250092
3251017
0100262
3250090
3251016
0101154
3251012
0101157
3150198
3250017
3250094
3251014