

Suction cup U8 Chloroprene, 3150116

- Suitable for objects with flat or slightly curved surfaces.
- Also used for concave objects.



General

Curve radius	6 mm
Movement, vertical max.	0.5 mm
Application	Plastic injection molded parts, Dry sheet metal
Material	Chloroprene (CR)
Suction cup model	U
Suction cup shape	Universal
Volume	0.1 cm ³
Weight	0.16 g

Fitting

Fitting size	None
Fitting style	None
Fitting type	None
Fitting option	None

Dimension

Height	7 mm
Outer diameter	9 mm

Performance — lifting forces

		
20 -kPa	1 N	1 N
60 -kPa	2.9 N	2.9 N
90 -kPa	3.9 N	3.4 N


Material

	Chloroprene (CR)
Colour	Black
Hardness	50 °Shore A
Temperature	-40 – 110 °C

Material resistance

	Chloroprene (CR)
Alcohol	++
Concentrated acids	-
Ethanol	N/A
Hydrolysis	++
Methanol	N/A
Oil	+
Oxidation	++
Petrol	+
Wear resistance	++++
Weather and ozone	++

Dimensional drawings



Values specified in the data sheet are tested at:

Room temperature	(20°C [68°F] ± 3°C [5.5°F])
Standard atmosphere	(101.3 [29.9 inHg] ± 1.0 kPa [0.3 inHg])
Relative humidity	0-100%
Compressed air quality	DIN ISO 8573-1 class 4

Accessories

	Item no.
Fitting M5 male, 5-8	3107031