



tandem closed  
compact  
lubrication hole M8 x 1

Dimensions in mm

Part-No.	∅ d	∅ D	A	H	h	L	E1	E2	E3	d1	N1	N2	M	weight (kg)
TAGC-12	12	19	40	33	17	60	35	29	30,0	4,3	11	16	M5	0,18
TAGC-16	16	24	45	38	19	65	40	34	32,5	4,3	11	18	M5	0,27
TAGC-20	20	28	53	45	23	65	45	40	32,5	5,3	13	22	M6	0,32
TAGC-25	25	35	62	54	27	85	55	48	42,5	6,6	18	26	M8	0,66
TAGC-30	30	40	67	60	30	105	70	53	52,5	6,6	18	29	M8	0,95
TAGC-40	40	52	87	76	39	125	85	69	62,5	8,4	22	38	M10	1,82
TAGC-50	50	62	103	92	47	145	100	82	72,5	10,5	26	46	M12	2,52

- Load ratings according to the specification of the bearing (x2)
- fixing screws DIN 912-8.8, circlip DIN 7980
- weight value considering the ball bushing

Ordering code

TAGC-	∅-	C-
tandem housing, closed, compact	shaft diameter	<b>C</b> linear ball bushing (refer to page 19) <b>FMT</b> linear slide bushing (refer to page 26)